

METALLIC FITTINGS

SEALTITE® COMPACT FITTINGS NICKEL PLATED BRASS **HEAVY DUTY** NPT FITTINGS



DESCRIPTION

- New compact design: 20% smaller and 35% lighter than standard SEALTITE® fittings. Ideal for tight spaces
- Excellent corrosion resistance, strength and durability
- IP 66/67 rated when installed with approved conduit and tightened to UL-514B/CSA C22.2 18.3 torque specifications
- Approved for both exposed and concealed locations

SPECIFICATIONS

- Nickel Plated Brass
- Colour: silver
- Temp. range: -45° C to + 105° C (-49° F to +221° F)
- CSA Approved to new Heavy Duty standard (CSA C22.2 No.18.3)
- UL Listed per UL 514B
- Marked 'HD' as required by CEC 2021
- Also available in Stainless Steel

APPLICATIONS


- Applications for high and low temperature where UL and CSA approvals are required
- Hazardous locations per CEC/NEC

SEALTITE®
FITTINGS

STRAIGHT:



Trade Size	Item ID	Min. Int. Bore	Dimensions mm				KO Size NPT	Weight kg(lb)/100	Std. Pkg.
			A	B	C	E			
1/2"	714.016.2-HD	14.5	36	14	29	27	1/2"	5.5 (12.1)	10
3/4"	714.020.2-HD	19.4	37	14	35	33	3/4"	7.8 (17.2)	5
1"	714.026.2-HD	24.7	40	16	45	42	1"	13.9 (30.6)	5
1-1/4"	714.035.2-HD	33.3	43	16	53	52	1-1/4"	18.6 (41.0)	2
1-1/2"	714.040.2-HD	38.0	50	18	62	60	1-1/2"	28.0 (61.7)	2
2"	714.050.2-HD	49.0	56	20	76	72	2"	44.0 (97.0)	2



90 DEGREE:



Trade Size	Item ID	Min. Int. Bore	Dimensions mm					KO Size NPT	Weight kg(lb)/100	Std. Pkg.
			A	B	C	D	E			
1/2"	714.916.2-HD	14.5	32	14	29	34	27	1/2"	10.1 (22.3)	10
3/4"	714.920.2-HD	19.4	36	14	35	40	33	3/4"	16.7 (36.8)	5
1"	714.926.2-HD	24.7	44	16	45	49	42	1"	29.6 (65.3)	5
1-1/4"	714.935.2-HD	33.3	49	16	53	53	52	1-1/4"	43.2 (95.2)	2
1-1/2"	714.940.2-HD	38.0	56	18	62	57	60	1-1/2"	59.5 (131.2)	2
2"	714.950.2-HD	49.0	66	20	76	68	72	2"	93.6 (206.4)	2

